



Rod/Line Weight Recommendations



Grain weights are calculated by the amount of line out beyond the rod tip while maintaining an anchor. Switch rod recommendations are for two-hand spey casting; subtract 60 grains for single-hand or overhead casting.

Model	Length	Line	Grain Window	Skagit G2	Skagit F.I.S.T.	Skagit Switch G2	Skagit SCOUT	Switch Streamer	Switch Float	Scandi Compact	Scandi Long	Rage Compact	Delta Spey II
E3 SR 6110	11' 0"	6	330-390	390	N/A	N/A	360	WF6	WF6	360	N/A	360	N/A
E3 SR 7110	11' 0"	7	390-450	450	450	N/A	420	N/A	N/A	420	N/A	420	N/A
E3 SR 8110	11' 0"	8	450-510	510	510	480	480	N/A	N/A	480	N/A	480	N/A
E3 TH 6127	12' 7"	6	390-480	450	450	N/A	420	N/A	N/A	420	N/A	420	6/7
E3 TH 7130	13' 0"	7	480-570	510	510	480	N/A	N/A	N/A	480	480	480	7/8
E3 TH 8134	13' 4"	8	540-630	570	570	540	N/A	N/A	N/A	540	540	540	8/9
KING 9130	13' 0"	9	630-720	660	660	N/A	N/A	N/A	N/A	N/A	N/A	N/A	9/10
KING 10130	13' 0"	10	720-810	750	720	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10/11
TR 3110	11' 0"	3	270-330	N/A	N/A	N/A	300	WF4	WF4.5	300	N/A	300	N/A
TR 4113	11' 3"	4	330-390	N/A	N/A	N/A	360	WF5	WF5.5	360	N/A	360	N/A
TR 6126	12' 6"	6	420-540	450	450	420	420	WF6	N/A	420	N/A	420	6/7
TR 7130	13' 0"	7	510-620	540	540	510	N/A	N/A	N/A	510	510	510	7/8
TR 8136	13' 6"	8	570-680	600	600	N/A	N/A	N/A	N/A	N/A	570	570	8/9
TR 9140	14' 0"	9	630-750	660	660	N/A	N/A	N/A	N/A	N/A	N/A	N/A	9/10
OHS 6104	10' 4"	6	190-210	N/A	N/A	N/A	210	N/A	WF3	N/A	N/A	N/A	N/A
OHS 7104	10' 4"	7	240-270	N/A	N/A	N/A	270	WF4	WF4	270	N/A	N/A	N/A
OHS 8104	10' 4"	8	300-330	N/A	N/A	N/A	330	WF4.5	WF4.5	330	N/A	330	N/A
SR 3106	10' 6"	3	150-210	N/A	N/A	N/A	210	N/A	WF3	N/A	N/A	N/A	N/A
SR 4106	10' 6"	4	210-270	N/A	N/A	N/A	270	WF4	WF4	270	N/A	N/A	N/A
SR 5108	10' 8"	5	270-330	360	N/A	N/A	330	WF5	WF5	330	N/A	330	N/A
SR 61010	10' 10"	6	330-390	390	N/A	390	360	WF6	WF6	360	N/A	360	N/A
SR 71010	10' 10"	7	390-450	450	450	450	420	WF7	N/A	420	N/A	420	N/A
SR 81010	10' 10"	8	450-510	510	510	480	480	WF8	N/A	480	N/A	480	N/A
Classic 5109	10' 9"	5	270-330	330	N/A	N/A	300	WF5	WF5	300	N/A	300	N/A
Classic 6110	11' 0"	6	330-390	360	N/A	N/A	360	WF6	WF6	360	N/A	360	N/A
Classic 7110	11' 0"	7	390-450	450	450	N/A	420	N/A	N/A	420	N/A	420	N/A
Classic 8110	11' 0"	8	450-510	510	510	480	480	N/A	N/A	480	480	480	N/A
Classic 6126	12' 6"	6	390-510	450	450	N/A	420	WF6	N/A	420	N/A	420	6/7
Classic 7129	12' 9"	7	480-570	510	510	480	N/A	N/A	N/A	480	480	480	7/8
Classic 8130	13' 0"	8	540-660	570	570	N/A	N/A	N/A	N/A	540	540	540	8/9
FG 6126	12' 6"	6	390-480	420	N/A	N/A	390	WF6	N/A	390	N/A	390	N/A
FG 7129	12' 9"	7	480-590	480	480	N/A	450	N/A	N/A	450	450	450	6/7
FG 8130	13' 0"	8	540-660	540	540	510	N/A	N/A	N/A	510	510	510	7/8
FG 3106	10' 6"	3	150-210	N/A	N/A	N/A	210	N/A	WF3	N/A	N/A	N/A	N/A
FG 4108	10' 8"	4	210-270	N/A	N/A	N/A	270	WF4	WF4	270	N/A	N/A	N/A
FG 6110	11' 0"	6	330-390	N/A	N/A	N/A	360	WF5.5	WF6	360	N/A	360	N/A
FG 7110	11' 0"	7	390-450	N/A	N/A	N/A	420	N/A	N/A	420	N/A	420	N/A

Custom Cut Sink Tip Specs

Size	Per Ft.	Sink	Length	Loop
T7	7 gr	7 ips	10' or 18'	White
T10	10 gr	8 ips	10' or 18'	Orange
T14	14 gr	9.5 ips	10' or 18'	Brown
T18	18 gr	11 ips	10' or 18'	Black
CCT 200	10 gr	8 ips	20' sink tip looped at both ends	
CCT 330	18 gr	11 ips		

Echo Ion Reel Specs

Size	Weight	Diameter	Width
7/9	7.9 oz.	3.9"	1.3"
8/10	8.3 oz.	4.1"	1.5"
10/12	9.3 oz.	4.7"	1.5"

PolyLeader Specs

Type	Sink	5'	8'	10'	14'
Float	0 ips	16 gr	N/A	26 gr	40 gr
Hover	0.5 ips	17 gr	24 gr	28 gr	N/A
Int.	1.5 ips	18 gr	25 gr	30 gr	38 gr
Slow Sink	2.6 ips	20 gr	26 gr	34 gr	N/A
Fast Sink	3.9 ips	22 gr	30 gr	38 gr	52 gr
Super Fast	4.9 ips	36 gr	52 gr	56 gr	64 gr
Xtra Sup. Fast	6.1 ips	44 gr	78 gr	88 gr	112 gr

Running Line Specs

Size	Diameter
20 lb Super-DRI Ridge	.036"
30 lb Super-DRI Ridge	.040"
20 lb Supple	.030"
30 lb Ridge Extreme	.040"
50 lb Ridge Extreme	.045"
30 lb Miracle Braid	.028"
30 lb IMPACT	.012"
44 lb IMPACT	.015"

